



TV80 0033

Product code: TV80 0033

Manufacturer: Twiga

In option, two audio inputs with microphone or line level are available.

Depending on camera model, component and SD composite analog video outputs are also available.

Camera video standard is coded with switches and a serial link (RS232 or TTL level) allows control of camera and audio setting.

FEATURES:

- SMPTE-424M 3G HDSDI Digital Interface
- Automatic SONY camera recognition
- Analog HD and SD video output
- Enhanced HDSDI signal quality : LOW jitter
- Video format selection by micro switch
- Embedded Colour bar & pathologic charts & Embedded color bar & reticle
- TTL or RS232 VISCA dialog level
- 5 to 12 VDC protected and EMC filtered power supply for interface and camera

APPLICATIONS:

- Broadcasting
- Industrial
- Security surveillance



Tecnosens S.p.A.
Via Vergnano,16 25125
Brescia (BS) Italia

Tel: (+39) 030 3534144
Fax: (+39) 030 3530815
info@tecnosens.it
PEC: tecnosens@legalmail.it

Power Supply	6 a 12 VDC, 6 W (camera included) 5V for SE600
Connector	BNC, (SMB, MCX, OPTIONS)
Dimension (mm)	48 (H) x 45 (L) x 20 (P)
Output protocol	3G-HD/SDI
Regulation	EMC FCC part 15, PCB: UL 94 V0
Working temperature	From 0°C to 60°C
Analogue Video Output	Y, Pb, Pr, 75 ohms, 1V